



UNIVERSAL POTENTIAL RELAYS SEPR60, SUPR & APR5

Replacing all potential relays, these universal potential relays offer the ultimate in convenience. Choose to “drop in” the wire to wire SUPR or the 2-wire SEPR60 or “dial in” the exact pick up voltage for the APR5.

SEPR60 Universal 2-Wire Potential Relay

- Voltage Sensitive Relay
- Instant Restart
- Safety Timeout: 1.0 to 1.5 Seconds
- Use with any suitable size Start Capacitor

SEPR60 Specifications

Operating Voltage	208 – 277 VAC, Single Phase
Amperage	40 Amps
Motor Power Rating	1 hp - 10 hp
Mounting	Non Positional
Terminals	Qty 3, 1/4" Male Spade

SUPR Universal Potential Relay

- Time Function Relay
- Start Time: 1.0 to 1.5 Seconds

APR5 Adjustable Potential Relay

- Voltage Sensitive Relay
- Adjustable Pick-up Voltage
- Safety Timeout 1.0 to 1.5 Seconds

APR5/SUPR Common Specifications

Operating Voltage	110 – 270 VAC, Single Phase
Amperage	30 Amps
Motor Power Rating	Up to 5 hp
Operating Position	Non-positional mounting.
Universal Mounting Bracket	Allows for easy installation. Unused portion of the bracket simply snaps off with pliers.
Terminals	Screw or push-on. Adapters to convert screw-on to push-on are provided.
Dimensions	1.75W x 2.25L x 1.50H



SEPR60



SUPR



APR5